



80262180



### S.x KNX (TP+EASY) Movement detector module 1,10m

#### Technical Features

##### Dimensions

|                                 |               |
|---------------------------------|---------------|
| Recommended installation height | 1.10 - 1.10 m |
|---------------------------------|---------------|

##### Settings

|                              |             |
|------------------------------|-------------|
| Supported configuration mode | ETS<br>easy |
| Minimal duty cycle           | 10 s        |

##### Functions

|                    |        |
|--------------------|--------|
| Maximal duty cycle | 30 min |
|--------------------|--------|

##### Connectivity

|                           |    |
|---------------------------|----|
| With bus system KNX radio | No |
|---------------------------|----|

##### Voltage

|                            |           |
|----------------------------|-----------|
| Operating voltage over bus | 21 - 32 V |
|----------------------------|-----------|

##### Scope of delivery

|                         |     |
|-------------------------|-----|
| Bus connection included | Yes |
|-------------------------|-----|

##### Electric current

|                                       |       |
|---------------------------------------|-------|
| Bus current consumption data transfer | 10 mA |
|---------------------------------------|-------|

##### Lighting

|                                |             |
|--------------------------------|-------------|
| Response brightness adjustable | 5 - 1000 lx |
|--------------------------------|-------------|

##### Detection

|                            |           |
|----------------------------|-----------|
| Detection angle adjustable | 45 - 90 ° |
| Detection angle horizontal | 90 - 180  |

##### Use conditions

|                       |            |
|-----------------------|------------|
| Operating temperature | -5 - 45 °C |
|-----------------------|------------|

##### Materials

|          |                  |
|----------|------------------|
| Material | Metal<br>Plastic |
|----------|------------------|

##### Texts

|                   |                                                                                                                                             |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Push button       | With button for automatic/permanent ON/permanent OFF                                                                                        |
| Operating mode    | With test mode<br>Master/slave operation for covering large detection areas<br>With 3 operating modes: automatic/permanent ON/permanent OFF |
| Function          | Presence simulation<br>With party function                                                                                                  |
| Installation mode | With spreader claws<br>With dismantling protection                                                                                          |

##### Reach distance

|                                   |      |
|-----------------------------------|------|
| Max. transmission range frontally | 12 m |
| Max. transmission range sideways  | 8 m  |

##### Sustainability

|              |     |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|